

Wireless Switch

The Prolojik GC861 (Single Rocker) and GC862 (Double Rocker) are universal, battery-less, piezoelectrically powered wireless switches in the European 55 x 55 form factor, available in a variety of finishes. The switch can be mounted either directly to the wall using wall screws or an adhesive patch, or into a standard UK backbox. The GC861/862 switches complement the Prolojik Go GL100 lighting control module, connecting wirelessly using the 2.4GHZ BLE network to control any of the 3 switch inputs of a Go LCM, allowing on/off switching and dimming.



Key Features

- Switching and dimming control
- Wireless connection to GL100 controllers
- 10m Range
- Various simple installation options
- Battery-less solution

Prolojik | Perspective House | 7 Cliveden Office Village | Lancaster Road
High Wycombe | Buckinghamshire HP12 3YZ | United Kingdom
+44 (0)1494 515100 | info@prolojik.com | prolojik.com

Wireless Switch

Specification

Wireless Specification

2.4GHz (Bluetooth Low Energy (BLE))
10m range

Power Supply

Electro-dynamic energy generator, maintenance free

Dimensions

50mm x 50mm x 14mm Rocker (LxWxH)
81mm x 81mm x 14mm Frame (LxWxH)

Conformity & Standards

EN 60 66 9
RED
FCC
ISED
ACMA

Environment

Storage
Temperature -25°C to +65°C
Humidity 0% - 95% non-condensing

In Use

Temperature -25°C to +65°C
Humidity 0% - 95% non-condensing

Technical Data

