

## Dali Plug-In Relay Module

Designed for easy installation, the Prolojik PL133 DALI plug in relay module c/w emergency test relay and DALI output. The module has been developed to complement Prolojik addressable lighting control modules and hubs.

The PL133 has been designed to suit a range of applications where DALI controls are not practical or cost effective.



### Key Features

- Luminaire switching & DALI dimming
- Available pre-addressed or addressable on site
- Compact form factor
- LED indication

---

Prolojik | Perspective House | 7 Cliveden Office Village | Lancaster Road  
High Wycombe | Buckinghamshire HP12 3YZ | United Kingdom  
+44 (0)1494 515100 | [info@prolojik.com](mailto:info@prolojik.com) | [prolojik.com](http://prolojik.com)

## Dali Plug-In Relay Module

### Specification

#### Network

DALI polarity insensitive 2mA consumption

#### Safety

EN 6 2368 1

#### Conformity & Standards

EMC immunity EN61000 6 1  
EMC emissions EN 61000 6 3  
DALI & NEMA compliant  
IEC Standard 62386 102  
NEMA Standard NS243 2004  
Supports DALI 2 & 3 byte protocol  
ARCOM MasterSpec 2013 Classification 29 09 43.16

#### Environment

Storage  
Temperature: 10°C to +60°C  
Humidity: 0% 90% non condensing

#### In Use

Temperature: 0 to +56°C  
Humidity: 10% 90% non condensing

#### Dimensions

150 mm x 90 mm x 40 mm (LxWxH)

#### Input

Mains supply: 230Vac +/- 10%; 50Hz  
Connections: input male socket for PC016M Wieland  
GST18i6 female plug

#### Output

Connections: output female socket for PC016 F  
Wieland GST18i6 male plug  
Switching capability: 1000VA maximum  
Maximum total load: 4A total load refer to Prolojik  
for load types

#### Features

Relay Status LEDs  
Power LED  
DALI LED  
Available pre addressed or addressable on site  
Compact form factor

### Technical Data



Prolojik | Perspective House | 7 Cliveden Office Village | Lancaster Road  
High Wycombe | Buckinghamshire HP12 3YZ | United Kingdom  
+44 (0)1494 515100 | info@prolojik.com | prolojik.com